Salcom 12-62 POCSAG VHF Paging Transmitter



PART NUMBER: **2547**

FEATURES

Simple operation and maintenance
Programable power output
Programable operating frequency
Over temperature cutout
Connects directly to cura¹ Paging Interface
Sends alarm messages to Alphanumeric Pagers
Red LED transmit indicator
Green LED power indicator

TECHNICAL SPECIFICATIONS

11 to 15 Vdc operation 40 mA standby, 1.2 A transmit
Operating frequency 148 -164 MHz.
Channel spacing 5, 6.25, 10, 12.5, 25 kHz
Output power 7 settings, 50 mW to 4 W
Modulation carrier FSK with NRZ data
Deviation +/-2.25 kHz or +/-4.5 kHz
Baud rate 512, 1200 Baud
Message format POCSAG
Dimensions 130 x 100 x 30 mm
4 external discrete inputs RJ45 connector
Serial data input RJ12 connector
Programming input mini usb connector
Approvals AS/NZS4769, EN 300 224, FCC Pt 90

ACCESSORIES

2548 POCSAG VHF Alphanumeric Pager, **2543** Paging Interface, **2404** Plug Pack,
2512 LED POCSAG Display (single sided), **2513** LED POCSAG Display (double sided)

cura1.com

cura¹ products are designed to augment well designed care programs and practices, cura¹ does not claim that any of its products are suitable as a substitute, or as a total solution for individuals that require care and constant supervision, and are at risk.