Wireless Output Falls Monitor



PART NUMBER: **2703**

FEATURES

Works as a transmitter for all Premium (corded) cura¹ devices with a RJ10 connection

Transmits alarm signals to cura¹ cordless monitors & receivers

Accepts 6.3 mm nurse call plug to trigger a nurse call alarm (optional)

Easy set pause, reset & volume controls

Delay settings (if enabled) of 2 seconds and 15 minutes

Low battery & input lost notifications

Powered by 3 x AA batteries (included) and / or 2406 Plug Pack 6V (optional)

Battery life is 6 months (nominal)

TECHNICAL SPECIFICATIONS

Power supply: 6 Vdc, 300 mA & / or 3 x AA alkaline batteries

Transmitter (included) has 30 m* range

Operating temp: 5°C to 40°C

Rel. humidity: < 85%

Housing material: ABS (UL-94HB, flammability grade)

Dimensions: 120 x 77 x 34 mm

Net weight: 140 g (without batteries), 200 g (with cover)

Pad / mat socket: RJ10

Adjustable volume: up to 108 db @ 10 cm

Voltage free contacts

ACCESSORIES

All **Premium, Universal** & **SnapOn** Pads & Mats (with a RJ10 plug), **2406** Plug Pack 6 V, **2544 & 2549** Multiport Expanders, **2561** Wireless Indicator Light, **2700** Six Channel Cordless Monitor, **2702** Three Channel Cordless Monitor, **3500R** ActiveCare Monitor, **3508** LED Pager, **3501** ActiveCare Pager, **3504** Mounting Bracket, **2742** Soft Monitor Cover, **2699** Fixing Strap

cura1.com

*The range of wireless devices may vary and be dependent on your specifc environmental conditions.
cura¹ products are designed to augment well designed care programs and practices, cura¹ does not claim that any of its products are suitable as a substitute, or as a total solution for individuals that require care and constant supervision, and are at risk.

PM125